

Soothers™

Moisturizing Earplugs

NRR
33
dB



6680 Soothers
Uncorded

MOISTURIZES FOR ALL DAY COMFORT

SOFT COMFORTABLE FIT

Moldex® Soothers foam earplugs are made of extra-soft, extra light foam. Their tapered shape fits easily in the ear canal, allowing them to seal gently and snugly without uncomfortable pressure. Plus, the outer surface of the earplug is smooth, so it doesn't irritate the ear canal. They're so comfortable you'll forget you're wearing earplugs.

INDEPENDENTLY TESTED: NRR 33

Soothers earplugs offer a high NRR 33, making them suitable for most noisy environments. So, while they look like fun, they provide serious protection.

FEATURES

- Moisturizes for all day comfort
- Soft foam and tapered shape for added comfort
- Highest independently tested NRR 33 rating
- Extra-soft, low-pressure foam for comfort and fit
- Tapered shape for easy insertion and removal
- Shaped to fit even very small ear canals
- Non-irritating smooth surface
- Look for the streaks and swirls as a symbol of Moldex quality
- 100% PVC-Free for a greener alternative

Glide Soothers

TWIST-IN FOAM

Moisturizing Earplugs

NRR
31
dB

6985 GLIDE Foam
Soothers with Cord

GLIDE SOOTHERS NOW AVAILABLE

Glide's unique multi-curved stem rotates for a custom fit inside each ear canal. With its unique curved stem design, you simply push & twist for Glide to angle its way to find your fit.

FEATURES & BENEFITS:

- Moisturizes for all day comfort
- Unique multi-curved stem rotates for a custom fit
- Large handle on curved stem for easy insertion & removal
- Glide Foam Soothers has the highest independently rated NRR for a no-roll earplug
- Cord can be attached at any desired length
- Look for the streaks and swirls as a symbol of Moldex quality
- 100% PVC-Free



6980 GLIDE Foam
Soothers without Cord



Made in U.S.A.

MOLDEX®
Ideas that wear well.™

Soothers™

Moisturizing Earplugs

PART # / DESCRIPTION	DISPLAY	CASE
6680 Soothers, Uncorded	200 Pairs per Box	10 Boxes per Case

ATTENUATION DATA

Tested According to ANSI Specs S3.19-1974 Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB)	37.5	36.7	42.2	40.3	39.3	42.3	44.6	46.6	45.9	NRR 33	CSA AL
Standard Deviation (dB)	5.5	4.4	3.5	3.2	2.8	3.0	3.1	2.8	2.8		

WARNING TO USER

1. Use these laboratory derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending upon how the protectors are fitted and worn.
2. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
3. Over protection can be dangerous. The wearer must be able to hear warning signals.
4. Wearers with hearing loss should exercise extreme caution.
5. It is the employer's responsibility to ensure that the type of hearing protector and its rating is appropriate for the user in their particular workplace.
6. Failure to follow all instructions and warnings could result in increased risk of hearing loss, serious injury or death.
7. Soothers foam earplugs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.
8. If irritation, redness or discomfort occurs, discontinue use and consult a licensed health practitioner.

MOLDEX TECHNICAL ASSISTANCE

Moldex provides all of the technical assistance required to set up a hearing protection program. For more information call +1 (800) 421-0668 or +1 (310) 837-6500 ext. 512/550 or E-mail: tech@moldex.com or visit www.moldex.com.

DISTRIBUTED BY:

MOLDEX®
Ideas that wear well.™

MOLDEX-METRIC, INC.

10111 Jefferson Blvd.
Culver City, CA 90232
TEL: +1 (800) 421-0668 or
+1 (310) 837-6500
FAX: +1 (310) 837-9563
E-mail: sales@moldex.com
www.moldex.com

CANADIAN CUSTOMER SERVICE

Tel: +1 (800) 421-0668, Ext. 550
Fax: +1 (310) 837-9563

Glide Soothers™

TWIST-IN FOAM

Moisturizing Earplugs

PART # / DESCRIPTION	DISPLAY	CASE
6980 Glide Foam Soothers Twist In Earplugs without Cord	100 Pairs per Box	4 Boxes per Case
6985 Glide Foam Soothers Twist In Earplugs with Cord	100 Pairs per Box	4 Boxes per Case

ATTENUATION DATA

Tested According to ANSI Specs S3.19-1974 by Michael & Assoc., State College, PA.

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000		
Mean Attenuation (dB)	35.5	37.0	42.5	39.9	39.5	40.0	40.5	43.4	45.6	NRR 31	CSA AL
Standard Deviation (dB)	4.5	4.2	4.9	4.1	3.3	4.3	3.4	3.8	3.9		

WARNING TO USER

1. Use these laboratory derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending upon how the protectors are fitted and worn.
2. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
3. Over protection can be dangerous. The wearer must be able to hear warning signals.
4. Wearers with hearing loss should exercise extreme caution.
5. It is the employer's responsibility to ensure that the type of hearing protector and its rating is appropriate for the user in their particular workplace.
6. Failure to follow all instructions and warnings could result in increased risk of hearing loss, serious injury or death.
7. Use caution when working around machinery or any other equipment to ensure neck cord does not become caught or entangled.
8. Glide foam earplugs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.

Keep earplugs away from infants and small children as they may get caught in the windpipe and create a choking hazard.

