

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1. SDS Revision Date: 01/18/2017

		1. PRODUCT & COMPANY IDENTIFICATION	
1.1	Product Name:	affresh® Stainless Steel Cleaning Spray	
1.2	Chemical Name:	Aerosol Spray; B-9845E	
1.3	Synonyms:	Stainless Steel Polish; W1042467	
1.4	Trade Names:	affresh® Stainless Steel Cleaning Spray	
1.5	Product Uses & Restrictions	Professional and Household Use	
1.6	Distributor's Name:	Whirlpool Corporation	
1.7	Distributor's Address:	2000 N. M-63, Benton Harbor, MI 49022	
1.8	Emergency Phone:	Poison Control Center (Medical): (866) 366-5048; CHEMTREC: +1 (800) 424-9300 /+1 (	703)527-3887
1.9	Business Phone:	1-800-643-0961 (USA), 1-888-253-2668 (CANADA)	
		2. HAZARDS IDENTIFICATION	
2.1	Hazard Identification:	This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia)	^

# to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia) WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. Classification: Aerosol level 1; Category 2 Flammable aerosol; Eye Irrit. 2

Hazard Statements (H): H-223 – Flammable Aerosol. H229 – Pressurized container: may burst if heated. H320 – Causes eye irritation.

Precautionary Statement (P): P210 – Keep away from heat, hot surfaces, sparks, open flames

<u>Precautionary Statement (P)</u>: P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking. P211 – Do not spray on an open flame or other ignition source. P251 – Do not pierce or burn, even after use. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P337+P313 – If eye irritation persists: Get medical advice/attention. P410+P412 – Protect from sunlight. Do not expose to temperature exceeding 50°C (122 °F). P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.





#### 3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
ISOBUTANE	75-28-5	200-857-2	1 - 10	Flam. Gas 1; H220
PROPANE	74-98-6	200-827-9	1 - 10	Press. Gas 1; Flam. Gas 1; H220

#### 4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		Skin:	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
		Eyes:	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes.  Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.
		Skin:	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
		Eyes:	Moderately irritating to the eyes.
		Inhalation:	Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion,



			and difficulty breathing. Inhalation of concentrate (e.g., drowsiness, dizziness, headaches, nausea).	ed vapors can cause nervous syste	em depression			
			(-3,4					
4.3	Symptoms of Overexposure	Ingestion:	May cause nausea, vomiting and/or diarrhea and	central nervous system depressio	on.			
			Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause					
		Skin:	allergic skin reactions (e.g., rashes, welts, dermat	itis) in some sensitive individuals.	Symptoms of skin			
			overexposure may include redness, itching, and in					
		Eyes:	Overexposure in eyes, may cause redness, itching	_ :	nage to eyes)			
Contact may cause mild eye irritation including s					1166			
		Inhalation:	Symptoms of overexposure can include coughing breathing.	, wheezing, nasal congestion, and	difficulty			
		Moderate irrita	tion to eyes and skin near affected areas. Additiona	ally, high concentrations of vapors	can cause			
.4	Acute Health Effects:		ziness, headaches and nausea.	,, ,				
			hronic health effects are expected to occur from a	single accidental ingestion. These	e ingredients may			
1.5	Chronic Health Effects:		kin and mucous membrane of the eye and respira me sensitive individuals. May also induce skin sen tis.					
1.6	Target Organs:	Eyes, skin, respi	ratory system.					
.7	Medical Conditions		zards may be delayed. Most common symptoms	HEALTH	1			
	Aggravated by Exposure	include irritatin	g properties to eyes, respiratory system and skin.	FLAMMABILITY	3			
			ological conditions (such as eczema) and	PHYSICAL HAZARDS	0			
			ditions (such as bronchial asthma and/or	PROTECTIVE EQUIPMENT	В			
		bronchitis) may	be exacerbated.	EYES SKIN				
	Fire and Explosion Hazards:	containers to pr aerosols are bu flammable liqui spraying them v	<b>5. FIREFIGHTING MEASURES</b> (NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile resting, stay clear until bursting is complete. Contain ds and/or exposed gases if exposed to the heat of with water until the fire has been extinguished.	bove 120° F. Cool uninvolved e hazards when bursting. If ners may rupture and release	3			
5.2	Fire and Explosion Hazards:  Extinguishing Methods: Firefighting Procedures:	containers to pr aerosols are bur flammable liqui spraying them of Water Fog, Foal As in any fire, wi demand_ and fir spray to cool fir from fire control waterway. Firef contained breat	(NFPA 30B). Aerosols may burst at temperatures a event possible bursting. Aerosols may be projectile rsting, stay clear until bursting is complete. Contain ds and/or exposed gases if exposed to the heat of the	bove 120° F. Cool uninvolved hazards when bursting. If hers may rupture and release fire. Keep containers cool by  Ing apparatus (pressure- hafter the fire is out. Use water hafter the fire is out. Use water hat re upwind. Prevent runoff water supply, or any natural happroved positive pressure self-	1 0			
5.2	Extinguishing Methods:	containers to price aerosols are bur flammable liqui spraying them with water Fog, Foar As in any fire, with demand and from fire contained breat decomposition	(NFPA 30B). Aerosols may burst at temperatures at event possible bursting. Aerosols may be projectile reting, stay clear until bursting is complete. Contain ds and/or exposed gases if exposed to the heat of the with water until the fire has been extinguished.  m, CO <sub>2</sub> , Dry Chemical  ear MSHA/NIOSH approved self-contained breathing ull protective gear. Keep containers cool until well at e-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking lighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazard	bove 120° F. Cool uninvolved hazards when bursting. If hers may rupture and release fire. Keep containers cool by high apparatus (pressure- hafter the fire is out. Use water if ire upwind. Prevent runoff water supply, or any natural happroved positive pressure self- ous combustion or	1 30			
5.1 5.2 5.3	Extinguishing Methods:	containers to private aerosols are but flammable liqui spraying them with the work of the	(NFPA 30B). Aerosols may burst at temperatures at event possible bursting. Aerosols may be projectile resting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of evith water until the fire has been extinguished. In CO2, Dry Chemical ear MSHA/NIOSH approved self-contained breathing protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking ighters must use full bunker gear including NIOSH-ining apparatus to protect against potential hazard products and oxygen deficiencies.	bove 120° F. Cool uninvolved hazards when bursting. If hers may rupture and release fire. Keep containers cool by  Ing apparatus (pressure- hater the fire is out. Use water hire upwind. Prevent runoff water supply, or any natural happroved positive pressure self- ous combustion or  JRES  Ip must wear appropriate Persona ding gloves and protective eyewer roduct and place into a container for haterial. Sweep up material using no plastic container or plastic liner we have your proposed and connel out of area. Stop spill or re-	ar. Use a non- for later disposal. on-sparking vithin another d away from spill d elease if it can be			
55.2	Extinguishing Methods: Firefighting Procedures:	containers to praerosols are bur flammable liqui spraying them was water Fog, Foal As in any fire, was demand_ and fire spray to cool fire from fire control waterway. Fireficontained bread decomposition  Before cleaning Equipment (PPE Small spills Weat combustible made Do not use water materials (e.g., container.  Large spills: Keet release. Isolate done with mining warrant.	(NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile reting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of the water until the fire has been extinguished.  In, CO <sub>2</sub> , Dry Chemical  ear MSHA/NIOSH approved self-contained breathing protective gear. Keep containers cool until well are-exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking ighters must use full bunker gear including NIOSH-ching apparatus to protect against potential hazard products and oxygen deficiencies.  S. ACCIDENTIAL RELEASE MEASU  any spill or leak, individuals involved in spill cleanurate in the proposition of t	bove 120° F. Cool uninvolved hazards when bursting. If hers may rupture and release fire. Keep containers cool by  Ing apparatus (pressure- after the fire is out. Use water if ire upwind. Prevent runoff water supply, or any natural approved positive pressure self- ous combustion or  IRES IP must wear appropriate Persona ding gloves and protective eyewer roduct and place into a container for aterial. Sweep up material using no plastic container or plastic liner we sonnel out of area. Stop spill or re including respiratory protection as	ar. Use a non- for later disposal. on-sparking vithin another d away from spill d elease if it can be			
5.3	Extinguishing Methods: Firefighting Procedures:	containers to private aerosols are bur flammable liqui spraying them with the work of the	(NFPA 30B). Aerosols may burst at temperatures a revent possible bursting. Aerosols may be projectile resting, stay clear until bursting is complete. Contained and/or exposed gases if exposed to the heat of with water until the fire has been extinguished.  In, CO <sub>2</sub> , Dry Chemical  ear MSHA/NIOSH approved self-contained breathing protective gear. Keep containers cool until well are exposed surfaces and to protect personnel. Fight of or dilution from entering sewers, drains, drinking ighters must use full bunker gear including NIOSH-thing apparatus to protect against potential hazard products and oxygen deficiencies.  S. ACCIDENTIAL RELEASE MEASU  any spill or leak, individuals involved in spill cleanural such as vermiculite or sand to soak up the prefer or a material such as "speedy dry" to soak up materials und plastic brooms, shovels, dustpans) and place into a princompatible materials (e.g., organics such as oil immediate hazard area and keep unauthorized per	bove 120° F. Cool uninvolved hazards when bursting. If hers may rupture and release fire. Keep containers cool by  Ing apparatus (pressure- after the fire is out. Use water if fire upwind. Prevent runoff water supply, or any natural approved positive pressure self- ous combustion or  JRES  Ip must wear appropriate Persona ding gloves and protective eyewer roduct and place into a container for plastic container or plastic liner w  away from spill. Stay upwind and resonnel out of area. Stop spill or re including respiratory protection as	ar. Use a non- for later disposal. on-sparking vithin another d away from spill o elease if it can be conditions			



7.2	Storage and Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F. Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying, keep cap in place when not in use. Storage level 2.									
7.3	Special Precautions:	Spilled material may	present a s	ipping hazar	d if left unat	tended. C	ean all spil	ls prom	ptly.		
		8. EXPOSU	<b>RE CON</b>	TROLS 8	<b>PERSO</b>	<b>NAL P</b>	ROTEC	TION			
3.1	Exposure Limits:		AC	CGIH		NOHSC		C	SHA	OTHER	
	Ppm (mg/m³)		TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		Chemical Name(s)  ISOBUTANE	600	750	NF	NF	NA	NA	NA	NA	
		PROPANE		NA	1000		NF				
8.2	Ventilation &	General mechanical	1000			NF Ifficient w		1000	NA in use 1	2100	r general
0.2	Engineering Controls	exhaust ventilation t									
8.3	Respiratory Protection:	No special respirator In instances where duse only protection a Canadian CAS Standa States, or Australia.	lusts of this authorized b	product are g y 29 CFR §19	generated, a 910.134, app	nd respira licable U.:	tory proted S. State reg	ction is ulations	needed, s, or the		
3.4	Eye Protection:	None required unde used when handling							uld be		<b>E</b>
8.5	Hand Protection:	None required unde sensitive individuals. nitrile or impervious	. When hand	dling large qu							
8.6	Body Protection:	No apron required w lbs.), eye wash static activities involving la soap and water.	on and delug	ge showers sh	nould be ava	ilable. Up	on complet	ion of v	vork		
		9. P	HYSICAI	. & CHEI	MICAL P	ROPE	RTIES				
9.1	Appearance:	Aerosol, Spray Foam									
9.2	Odor:	Fresh Fruit									
9.3	Odor Threshold	NA									
9.4	pH:	6.0 – 8.0									
9.5 9.6	Melting/Freezing Point Initial Boiling Point/	NA NA									
9.7	Boiling Range: Flashpoint:	-30 °F (-34 °C) TCC fc	or propellant	only.							
9.8	Upper/Lower Flammability limits	NA	propendin	. Jinyi							
9.9	Vapor Pressure:	@ 20 °C (68° F) – Car	n pressure n	ot to exceed	180 psig @	55 °C (131	°F) 12.4 ba	ar			
0.10	Vapor Density	>1									
	Relative Density:	0.95 – 1.005									
	Solubility:	Soluble									
	Partition Coefficient (log Pow):	NA									
	Autoignition Temperature:	NA									
	Decomposition Temperature.	NA									
	Viscosity:	Aerosol at ambient t	•								
9.17	Other Information:	Evaporation Rate >1	. Percent Vo	nathe < 12%							



		10. STABILITY & REACTIVITY
10.1	Stability:	Stable at normal temperatures.
0.2	Hazardous	
	Decomposition	Oxides of carbon (CO, CO <sub>2</sub> ) and sulfur (SO <sub>2</sub> )
	Products:	
0.3	Hazardous	Will not occur
	Polymerization:	Will not occur.
0.4	Conditions to Avoid	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.
10.5	Incompatible Substances	Mixture with strong acids, alkalis or oxidizers.
	·	
		11. TOXICOLOGICAL INFORMATION
1.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestio YES YES
1.2	Toxicity Data:	This product was not tested on animals. Toxicology data, found in scientific literature, is available and not presented
		this document.
1.3	Acute Toxicity:	See Section 4.4
	Chronic Toxicity:	See Section 4.5
	Suspected Carcinogen:	No.
1.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.
	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.
1.7	Irritancy of Product:	See Section 4.3
	Biological Exposure	
	Indices:	NA
11.9	Physician	
	Recommendations:	Treat symptomatically.
		12. ECOLOGICAL INFORMATION
12.1	Environmental Stability:	There is no specific data available for this product.
	Effects on Plants & Animals	There is no specific data available for this product.
12.3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.
		40 0100001 001010010
		13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and
		appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with
		local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed
		facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.
13.2	Special Considerations:	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)
		14. TRANSPORTATION INFORMATION
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or
		CONSUMER COMMODITY, ORM-D (IP VOL < 1.0 L) – until 12/31/2020
L4.2	IATA (AIR)	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL < 0.5 L); or
		ID8000, CONSUMER COMMODITY, ORM-D (IP VOL < 0.5 I=L)
	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)
L4.3	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL <_ 1.0 L); or
	rbon (canadian divb).	MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"
	TBGN (Canadian GNB).	White the control of
14.4	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)
14.4 14.5		<b>▼</b>
14.4 14.5 14.6	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)



15.1	SARA Reporting Requirements:	This product does not contain any substance subject to SATA Title III, section 313 reporting requ	uirements.			
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.				
15 3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.				
	CERCLA Reportable					
	Quantity (RQ):	NA				
15.5	Other Federal	This product complies with the appropriate sections of the Food and Drug Administration's 21 C	FR Subchapter G.			
	Requirements:	(Cosmetics)				
15.6	Other Canadian	This product has been classified according to the hazard criteria of the CPR and the SDS				
	Regulations:	contains all of the information required by the CPR. The components of the product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substance List. WHMIS Class B5 (Flammable Aerosol)	<b>(*)</b>			
15.7	State Regulatory Information:	Isobutane is found on the following state criteria lists: Massachusetts Hazardous Substances List Right-to-Know list (PA), New Jersey Right-to-Know List (NJ).	t (MA), Pennsylvania			
		<u>Propane</u> can be found on the following state criteria lists: MA, MN, PA, WA and NJ.				
		No other ingredients of this product, present in a concentration of 1.0% or greater, are listed on state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substance Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Subst Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin H List (WI).	Florida Toxic es List (MI), Minnesota ances List (NY),			
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: <u>Isobutane:</u> Flammable (F). <u>Risk Phrases (R)</u> 12 – Highly Flammable. <u>Safety Phrases (S)</u> : 2-9-16  – Keep out of reach of children. Keep container in a well-ventilated area. Keep away from sources of ignition – No smoking. <u>Propane</u> : : Flammable (F). Risk Phrases (R) 12 – Highly Flammable. Safety Phrases (S): 2-9-16  – Keep out of reach of children. Keep container in a well-ventilated area. Keep away from sources of ignition – No smoking.	×			
		16. OTHER INFORMATION				
16.1	Other Information:	WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED, HIGHLY AND VAPOR. CAUSES EYE IRRITATION. Keep away from heat, hot surfaces, sparks open flames sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or be avoid breathing vapor/spray. Wash thoroughly with soap and water after handling. Use only in a Wear eye protection. Protect from sunlight. Do not expose to temperature exceeding 50 °C (122 Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation person divice/attention. KEEP OUT OF REACH OF CHILDREN.	and other ignition ourn, even after use. a well ventilated area. 2°F). IF INHALED: h water for several			
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.				
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § government regulations must be reviewed for applicability to this product. To the base of Whirl knowledge, the information contained herein is reliable and accurate as of this date; however, a completeness are not guaranteed and no warranties of any type, either expressed or implied, an information contained herein relates only to the specific product(s). If this product(s) is combine all component properties must be considered. Data may be changed from time to time. Be sure edition.	pool Corporation's accuracy, suitability or re provided. The ed with other materials,			



Flammable	Explosive	Oxidizer
Pressurized	Corrosive	Toxic
Harmful/Irritating	Health Hazard	Environment
Face Shield and Protective	Apron	Dust Mask
Eyewear	Protective Clothing	Full Suit
Boots	Safety Glasses	Gloves



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.

SDS Revision Date: 01/18/2017

Full Face Respirator	Reactive	Irritant / Harmful
Biohazard	Oxidizing	Flammable
Infectious	Corrosive	Compressed
Toxic	Irritation	